## **Bolton Technical Rondo 5G**

Low Profile 75 Ohm Dome Building Antenna



## BT478720

The Rondo provides powerful wide-band coverage while offering up to +6 dBi gain. Great for open office spaces, open home floor plans, and for providing coverage while using a minimalist, discrete design.

- Typically both used in indoor distribution of GSM/CDMA
- 5G/4G/3G/LTE services
- Low return loss, Stable performance
- Compact, lightweight and easy to install



ELECTRICAL STUFF	Product Specifications may change without prior notice.						RADIATION	
Item No.	BT478720						PATTERNS	
Frequency Range	MHz	617-806	806-960	1350-1550	1690-2700	3300-3800	4900-6000	HORIZONTAL
Gain	dBi	1.5±0.5	2.2±0.5	3.5±0.5	4.5±1.0	6.0±1.0	6.0±1.0	
VSWR		≤1.8	≤1.8	≤1.8	≤1.8	≤1.8	≤1.8	
Polarization		Linear						900 MHz
PIM, 3rd Order, 2 x 20 W					≤-153			
Input Power, maximum		watt			50			
Impedance		ohm			75			1710 MHz

## MECHANICAL STUFF

Connector Type		F-Female
Size	mm, in	220 x 18, 8.66 x 0.70
Antenna Weight	kg, lb	0.30, 0.66
Operational Temperature	oC, oF	-55 to 60, -67 to 140
Operational Humidity	%	< 95
Radome Material and Color		ABS, White, RAL9003 / Pantone 705
Ingression Protection Rating		IP65
Mounting Kit		Ceiling, via hole (standard)
Cable Length	cm, in	30, 11.81
Соах Туре		RG141



☑ sales@boltontechnical.com
⊕ www.boltontechnical.com

5010 Wright Road, Suite 115
Stafford, TX, 77477